



SHACMAN

X30006X4 Tractor Main Specifications

Modele		SX42574V324C
GCW (kg)	55000	
Curb mass (kg)	8800	
Max. Grade Ability (%)	27%	
Min. Ground Clearance (mm)	315	
Appearance dimensions (mm)	Length	6825
	Width	2490
	Height	3650
Wheel base (mm)		3175+1400
Front/Rear Overhang		1525/725
Emission Standards		EuroIII
The max speed (Km/h)		90
Engine	Model	CUMMINS ISME420 30 EURO III
	Max power(kW/rpm)	308/1900
	Max torque(n.m/rpm)	2010N.m/1200
	Type	Diesel 6-cylinder in line, 4-stroke, water cooling, with turbo charging and inter-cooling
	Displacement (L)	10.8
Gearbox	Transmission	FAST BRAND Model: F16JZ24A with PTO
	Type	AMT
	Speed	F16&2R

	Ratio	12.1/9.41/7.31/5.71/4.46/3.48/2.71/2.11/1.64/1.28/1.00/0.78 R1:11.56 R2:2.59
Steering		ZF 8098 steering .
Clutch		EATON ϕ 430 diagram spring
Cab		SHACMAN X3000, high roof cab. X3000 with deflector
		driver seat with air suspension
		two sleeping bed
Air filter		Fleetguard Air filter
Air-conditioner		Automatic A/C
Front axle		7.5T MAN
Suspension		Front& Rear less-leaf spring
Rear axle		13T MAN, single reduction driving axle with inter-wheel differential and differential lock.Ratio: 4.111
Brake System	Type	Drum
	Service	With dual-circuit compressed air brake
	Parking	Power spring brake acting on rear wheel
	Auxiliary Brake	JACOB WABCO 4 channel ABS
Tire		315/80R22.5 with one spare tire
Battery		24V 、 180Ah
Fuel tank capacity (L)		600+300L Aluminum Tank with cover.
Equipment		Rear windows, electrical window lifter , four points air suspension cab, electrical hydraulic reversal cab, with USB, play radio with MP3 forma, Fiberglass reinforced plastic bumper, E-Tachograph, Cruise control
Fifth Wheel		JOST 50#

