



# SHACMAN

## F3000 6X4 MALAXEUR

### Main Specifications

Model		SX5255GJBDR384	
Gross vehicle weight (kg)		26000	
Curb mass (kg)		13200	
Max. speed (km/h)		80	
Min. turning circle (m)		24	
Min. ground clearance (mm)		314	
Max. gradeability(%)		30	
Dimensions (mm)	Length	9460	
	Width	2490	
	Height	3880	
Wheel base (mm)		3775+1400	
Overhang (mm)	Front	1525	
	Rear	2760	
Engine	Model	WEICHAH WP10.340E22+PTO	
	Max power (kW/rpm)	250/2200	
	Max torque(n.m/rpm)	1400/1200~1400	
	Displacement (L)	9.726L	
Clutch		EATON Φ 430 diaphragm-spring type	
Gearbox		FAST 9 RTD11509C	
Steering		ZF technology	
Front axle		9.5 ton front axle with MAN technology	
Frame (mm)		850×300 (8+7)	
Suspension		Multiple leaf springs front and rear+4U-bolt	
Rear axle		13 MAN Double reduction driving axle with inter-wheel differential and differential lock Ratio:5.262	
Auxiliary Brake		6 channel ABS	
Tire		315/80R22.5 (Quantity: 11)	
Cab		F3000 Extended Cab with Flat Roof	
		Hydraulic seat	
		4 Point hydraulic Suspension cab	
Air-conditioner		Hot Zone Air Condition	
Air filter		Oil bath filter	
Battery		24V、165Ah	
Fuel tank	Volume (L)	400L	
	Material	Aluminum	
Standard equipment		Driving recorder, manual flipping of the cab, three-level access pedal, metal bumper with illuminated grille, electric window shaker, taillight protection, water tank protection, reversing buzzer, spare tire rack	
Mixer	Capacity (m <sup>3</sup> )	9	

