

## **SHACMAN**

## F3000 6X4 Dump Truck Main Specifications

Model			SX3255DR384	
Gross vehicle weight (kg)		26000	3500 75 8.3 285	
Curb mass (kg)		13500		
Max. speed (km/h)		75		
Min. turning circle (m)		8.3		
Min. ground clearance (mm)		285		
Max.gradeability(%)		30		
Dimensio (mm)	Length		8175	
	Width	2490		
	Height	3450		
Wheel base (mm)		3775+1400		
	Model	WP10.340E22 Euro II		
<b>.</b>	Max power (kW/rpm)	250/2200		
Engine	Max torque(n.m/rpm)	1400/1200-1600		
	Displacement (L)	9.726L		
Clutch		EATON Φ 430 diaphragm-spring type		
Gearbox		FAST 9_RTD11509C- Iron shell -QH50		
Steering		ZF technology Chinese brand steering		
Front axle		9.5T front axle with MAN technology		
Frame (mm)		850×300 (8+7)		
Suspension		Multi-leaf spring of front and rear suspension+4U-bolt		
Rear axle		16T MAN Double reduction driving axle with inter-wheel differential and		
		differential lock Ratio:5.92		
Tire		12R22.5 (Quantity: 11)		
Cab		F3000 series cabin of middle length with flat roof		
		Hydraulic seat		
		4 Point hydraulic Suspension cab		
Air-conditioner		Hot zone air condition		
Air filter		Oil bath filter		
Battery		24V、165Ah		
Fuel tank	Volume (L)	400L		
	Material	Aluminum alloy		

PTO		QH50	
Standard equipment		Oil pan protective grille, metal bumper-lighted grille, manual tilting of the cab	
		electric window shaker, three-level entry pedal	
	Size (mm)	5200*2300*1350	
	Thickness (mm)	Bottom 10 Side 6	
Cargo	Way of Lifting	Mid Lifting with hydraulic lifting system	
	Oil cylinder model	T typeΦ220	
	Type	Rectangular bucket	



