



Model		SX41855X361		
GCW (kg)		44000		
Curb weight (kg)		8500	-	
Max. Grade Ability (%)		35	BRAILTAN Xourr	
Min. Ground Clearance (mm)		315		
Dimension	Length	6150		
(mm)	Width	2490		
	Height	3890		
Wheel base (mm)		3600		
Front/Rear Overhang		1525/1025		
	Model	WP12.460N		
Enging	Max power (kw/rpm)	338/1900		
Engine	Max torque(n.m/rpm)	2110/1000~1400		
	Displacement (L)	11.596		
Gearbox		ZF 12TX2421TD		
Steering		ZF technology		
Clutch		EATONΦ430 diaphragm-spring type		
Cab		SHACMAN X5000 flat-top cab		
		Driver seat with air suspension		
		One sleeping bed		
Air filter		FLEETGUARD Air filter		
Air-conditioner		Automatic A/C		
Front axle		7.5T MAN		
Suspension		Air suspension with ECAS		
Frame (mm)		(940-850)×300 (single 8)		
Rear axle		13T MAN, Single reduction driving axle with inter-wheel differential and differential lock. Ratio:2.846		
Tire		315/80R22.5 with one spare tire		

Battery	24V、165Ah	
Fuel tank capacity (L)	700L Aluminum Tank with cover	
	Multi-function steering wheel, driving recorder, electric cab tilt, three-level entry	
Equipment	pedal, fiberglass bumper, electric window shaker, central locking (with remote	
Equipment	control), electric heated rearview mirror, with hydraulic retarder, WABCO EBS+ESC,	
	With spare tire rack, Magnesium aluminum alloy wheels	
Fifth Wheel	JOST 50	

