




# SHACMAN

## X3000 6X4 Tractor Main Specifications

Model		SX42555X324	
GCW (kg)	49000		
Curb weight (kg)	8800		
Max. Grade Ability (%)	27%		
Min. Ground Clearance (mm)	315		
Appearance dimensions (mm)	Length	6825	
	Width	2490	
	Height	3650	
Wheel base (mm)		3175+1400	
Front/Rear Overhang		1525/725	
Emission Standards		Euro II	
The max speed (Km/h)		90	
Engine	Model	WP12.460N	
	Max power(kW/rpm)	338/1900	
	Max torque(n.m/rpm)	2110/1000~1400	
	Displacement (L)	11.596	
Gearbox		SF16JZ220A	
Steering		ZF 8098 steering	
Clutch		EATON $\phi$ 430 diagram spring	
Cab	SHACMAN X3000 flat-top cab with deflecteur		
	Driver seat with air suspension		
	One sleeping bed		
Air filter		FLEETGUARD Air filter	
Air-conditioner		Automatic A/C	
Front axle		7.5T MAN	
Suspension		Front& Rear less-leaf spring	
Rear axle		13T MAN, Double reduction driving axle with inter-wheel differential and differential lock. Ratio: 3.866	
Tire		315/80R22.5 with one spare tire	

Battery	24V、 165Ah
Fuel tank capacity (L)	700+230L Aluminum Tank with cover
Equipment	Multi-function steering wheel, driving recorder, electric cab tilt, three-level entry pedal, fiberglass bumper, electric window shaker, central locking (with remote control), electric heated rearview mirror, WABCO imported four-channel ABS_ASR, FHB400 hydraulic retarder
Fifth Wheel	JOST 50

