

## **SHACMAN**

## F3000 8X4 MALAXEUR Main Specifications

Model			SX5315GJBDT306		
Gross vehicle weight (kg)			32000		
Curb mass (kg)			15500		
Max. speed (km/h)			75		
Min. ground clearance (mm)			285	SHACHAN	
Max.gradeability(%)		30			
	Len	gth		10300	
Dimension (mm)	ns Wic	lth		2490	
(2222)	Hei	ght	3990		
Wheel base (mm)		1800+2975+1400			
Rear Overhang (mm)		2600			
Engine	Model		WP10.380E22+PTO EURO II		
	Max power (kW/rpm)		280/2200		
	Max torque(n.m/rpm)		2000		
	Displacement (L)		9.726L		
Clutch		EATON Φ 430 diaphragm-spring type			
Gearbox			FAST 10JSD180		
Steering			ZF technology		
Front axle		MAN 9.5T			
Frame (mm)			850×300 (8+7)		
Suspension		Multiple leaf springs front and rear+4U-bolt			
Rear axle		16 MAN Double reduction driving axle with inter-wheel differential and differential lock Ratio:5.262			
Tire		315/80R22.5 (Quantity: 13)			
Cab		F3000 Mid-length flat-roof cab			
		Hydraulic seat			
		4 Point hydraulic Suspension cab			
Air-conditioner		Hot zone air conditioning			
Air filter		Oil bath filter			
Battery		24V、165Ah maintenance free			
Fuel tank	Volume (L)		400L		
I del tulik	Material		Aluminum alloy		
Standard equipment		Six-channel ABS, driving recorder, manual tilting of the cab, three-level entry pedal, metal bumper with illuminated grille, electric window shaker, reflective vest, seat belt not fastened reminder			
Mixer Capacity (m3)			12		



