

## **SHACMAN**

## L3000 4X2 Chassis Main Specifications

Model		SX11858J571		
Gross vehicle weight (kg)		19000		
Curb mass (kg)		6000	90 17/8.4 290	
Max. speed (km/h)		90		
Approach / departure angle (°)		17/8.4		
Min. ground clearance (mm)		290		
Max.gradeability(%)		30		
Length			9340	
Dimension	ns Width	2468		
(mm)	Height	2975		
Wheel base (mm)		5700		
Overhang Front		1340		
(mm)	Rear	2300		
	Model	WP6.210E32 Euro II		
	Max power (kW/rpm)	210/2300		
Engine	Max torque(n.m/rpm)	800/1400~1600		
	Displacement (L)	6.75L		
Clutch		Φ395 diaphragm-spring type		
Transmission		FAST 8JS85TM-Aluminum shell-QD40J		
Gearbox	Gear ratio	F8&R2		
Steering		ZF technology		
Front axle		4.8t disc brake front axle		
Frame (mm)		870×250 (7+4)		
Suspension		Multi-leaf spring of front and rear suspension		
Rear axle		10 MAN Single-stage reduction rear axle-4.625		
Tire		11R22.5 (Quantity: 7)		
Cab		L3000 cab with air deflector		
		Hydraulic seat		
		Hydraulic Suspension cab		
Air-conditioner		Electronic controlled air condition		
Battery		24V、135Ah		
Fuel tank	Volume (L)	300L		
Material Material		Aluminum		
Standard equipment		Aluminum water tank, tachograph, electric tilting of the cab, two-level entry		

pedal, electric window shaker, central locking (with remote control), hydraulic
main seat - add a third seat, electric heated rearview mirror, LED daytime
running lights, reflective vest, seat belt not fastened reminder (main driver +
co-pilot), cruise control system

